Beam Power Tube

NOVAR TYPE

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:		
Voltage (AC or DC)	6.3 ± 10%	volts
Current at 6.3 volts	1.2	amp
Mu-Factor, Grid No.2 to Grid No.1 for plate volts = 150, grid-No.2 volts = 150, grid-No.1 volts = −22.5	4.4	
Direct Interelectrode Capacitances (Approx.):[a]		
Grid No.1 to plate	0.26	μμf
Grid No.1 to cathode & grid No.3, grid No.2, and heater	15	μμf
Plate to cathode & grid No.3, grid No.2, and heater	6.5	μμf

Characteristics, Class A_1 Amplifier:

Plate Voltage	60	250	volts
Grid-No.2 Voltage	150	150	volts
Grid-No.1 Voltage	0	−22.5	volts
Plate Resistance (Approx.)	−	15000	ohms
Transconductance	−	7100	μmhos
Plate Current	390[b]	70	ma
Grid-No.2 Current	32[b]	2.1	ma
Grid-No.1 Voltage (Approx.) for plate ma. = 1	−	−42	volts

Mechanical:

Operating Position	Any
Maximum Overall Length	3.55"
Seated Length	3.04" ± 0.13"
Diameter	1.438" to 1.562"
Bulb	T12
Cap	Skirted Miniature (JEDEC C1-2 or C1-3)
Socket	Cinch Mfg. Co. No.149 1900 24, Industrial Electronic Hardware Co. No.SO-0968-M, or equivalent
Base	Large-Button Novar 9-Pin (JEDEC No.E9-76)
Basing Designation for BOTTOM VIEW	9NM

Pin 1 - Grid No.2
Pin 2 - Grid No.1
Pin 3 - Cathode, Grid No.3
Pin 4 - Heater
Pin 5 - Heater
Pin 6 - Grid No.1
Pin 7 - Grid No.2
Pin 8 - Do Not Use
Pin 9 - Do Not Use
Cap - Plate

HORIZONTAL-DEFLECTION AMPLIFIER

Maximum Ratings, *Design-Maximum Values:*

For operation in a 525-line, 30-frame system[c]

DC PLATE-SUPPLY VOLTAGE	770	max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE[d]	6500	max.	volts
PEAK NEGATIVE-PULSE PLATE VOLTAGE	1500	max.	volts
DC GRID-No.2 (SCREEN-GRID) VOLTAGE	220	max.	volts
DC GRID-No.1 (CONTROL-GRID) VOLTAGE	-55	max.	volts
PEAK NEGATIVE-PULSE GRID-No.1 VOLTAGE	330	max.	volts
CATHODE CURRENT:			
Peak	550	max.	ma
Average	175	max.	ma
GRID-No.2 INPUT	3.5	max.	watts
PLATE DISSIPATION[e]	17.5	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200[f]	max.	volts
BULB TEMPERATURE (At hottest point on bulb surface)	240	max.	°C

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:			
For grid resistor-bias operation	1	max.	megohm

[a] Without external shield.


[b] This value can be measured by a method involving a recurrent wave form such that the maximum ratings of the tube will not be exceeded.

[c] As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations," Federal Communications Commission.

[d] This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one horizontal scanning cycle. In a 525-line, 30-frame system, 15 per cent of one horizontal scanning cycle is 10 microseconds.

[e] An adequate bias resistor or other means is required to protect the tube in the absence of excitation.

[f] The dc component must not exceed 100 volts.



* APPLIES IN ZONE STARTING 0.375" FROM BASE SEAT.

AVERAGE CHARACTERISTICS

